

PyroFlare

Automatic Flaring for Pyrolysis Gas

Today, Tyre Pyrolysis has become synonymous with pollution and plants are being made to shut down everywhere. Its about time that preventive measures are taken to protect the industry from agitators or actions by Pollution Control Boards. The biggest cause of pollution in Tyre Pyrolysis Industry is excess gas being released in the air. The smell is so strong and nauseating that the whole neighbourhood is turned against the plant.

Greenmor is happy to offer an effective solution for this problem. PyroFlare, the automatic flaring system, that not only burns the excess gas and eliminates the bad odour, but also maintains process pressures at required levels.

Product Highlights:

- + Fully Automatic
- + Bypass switch
- + 100db Hooter
- + Stainless steel flare
- + Easy installation.
- + Automatic pressure maintenance
- + Built-In anti-flashback system
- + Large LED display
- + Easily programable

Technical Specifications:

Input Voltage	230V
Controller Dimensions:	250 (L) x 160 (W) x 160(H) mm
Flare Legnth	1800 mm
Operation:	Micro-Processor Controlled
Display	Segment LED
Ignition System:	Automatic (Additional Manual Bypass)
Hooter:	100 Db
Pressure Transducer:	0-6 Bar

Technical specifications are subject to change.

Rs.53700/-

Taxes, Freight and Installation Extra.
Subject to change.
Ascertain while placing the order.

Brought to you by Greenmor Energy Product Pvt Ltd. For enquiries, contact:
Ph: 0141 2812827; +91 9982295455 / Email: pyro@greenmor.in / Web: www.greenmor.in